


# i550 Measurements

 Edit this form

Use Instructions pdf available from the Class website. Measurements in inches unless noted.

\* Required

**Hull Number \***

**Hull Skin Length \***

(This method adds 0.5" for the length along the curved bottom surface)

**Rocker \***

Depth of hull bottom curve, from bow to stern.

**Sheer Width, Transom \***

**Sheer Width, 90" forward of Transom \***

**Jig Vertical Gap at Arrow, Transom \***

**Jig Lateral gap between Arrow marks, Transom \***

**Jig Vertical gap at Arrow, 90" forward of Transom \***

**Jig Lateral gap at Arrow marks, 90" forward of Transom \***

**Chine Width, 6" aft of Bow \***

**Bow Height (Freeboard), 6" aft of Bow \***

**Hull Sides, Max Outward/Inward Deviation from a straight line, Chine to Sheer \***

**Cabin Height adjacent to Mast Step \***

above hull bottom

**Distance, Mast Butt to Cabin Top \***

(used with rig dimensions, below)

**Keel Depth \***

Below hull bottom

**Keel Bulb Width \***

**Keel Bulb Height \***

**Keel Weight \***

Bulb and Fin

**Boat Weight in Measurement Condition \***

**Corrector Weights \***

Optional "free" 20# used?

☐ yes

☐ no

**Additional Corrector Weights, amount \***

(pounds, enter "0" if not applicable)

**Additional Corrector Weights, fore and aft separation \***

(inches, enter "0" if not applicable)

**Flotation Amount Provided \***

Cubic Feet

**Distance, Mast Butt to bottom of Band 1 \***

**Distance, Mast Top to bottom of Band 1 \***

**Distance, top of Boom to bottom of Band 1 \***

**Distance, Mast Butt to bottom of Band 2 \***

**Distance, Mast Butt to Forestay intersection with forward face of Mast \***

**Distance, Upper Surface of Spinnaker Sheave above Band 1 \***

(Use negative number for distance BELOW Band 1, if applies)

**Depth of Mast Track from aft face of Mast \***

**Distance to Band 3 from aft face of Mast \***

**Distance aft of Bow to intersection of Forestay with Deck \***

(positive number if AFT of Bow, negative number if FORWARD of Bow)

**Distance, Bow to forward face of Mast \***

(at mast step or aft-most Partner position, as applies)

**Distance, Bow to Tackline when held vertically \***

(with Pole fully extended and centered)

**Mainsail max girth \***

(length of flaked or rolled sail)

**Mainsail head angle \***

(measured to upper 3' of Luff)

Never submit passwords through Google Forms.

Powered by



This content is neither created nor endorsed by Google.

[Report Abuse](#) - [Terms of Service](#) - [Additional Terms](#)